



Always Moving Forward®

Corporate Headquarters
PO Box 66800
St. Louis, MO 63166-6800
888-237-7611 | 618-337-6000
cerroflow.com

June 1, 2015



SUBJECT: Cerro Flow Products are UL Recognized to 701 PSI Operating Pressures, to support R410A Refrigerant Requirements.

TO: Our Valued Customers

This letter is to confirm Cerro’s compliance to UL 207 – Standard for Refrigerant-Containing Components and Accessories, Non-Electrical CAN/CSA C22.2 No. 140.3-09 – Refrigerant-Containing Components for use in Electrical Equipment, along with the applicable ASTM specifications. This compliance aligns with the requirements of the Canadian Standard for Refrigeration Equipment.

The following products have been tested through Underwriters Laboratories (UL) and are certified to operating pressures of 701psi at a continuous operating temperature of 250°F.

Product	Type	Shape	Diameters
Copper Tube	REFER	Coils	1/8" thru 1-1/8"
	ACR	Hard Lengths	3/8" thru 1-3/8"
	K	Straight Lengths	1/4" thru 2-1/2"
	Line Sets	Insulated Coils	1/4" thru 1-1/8"

For additional information, please see the UL Online Certifications Directory at www.ul.com/database.

Cerro continues its commitment to delivering high quality products and superior customer service.

Plumbing and mechanical codes govern what types of products may be used for applications. Local codes should always be consulted for minimum requirements.

~ALL TERMS AND CONDITIONS OF SALE APPLY AND THIS LETTER DOES NOT CHANGE, ALTER OR OTHERWISE MODIFY THOSE TERMS AND CONDITIONS~